

OLTCIT club



DESIGN : front-located engine ; front drive ; monocoque self-supporting body made of steel sheet processed by electropriming to resist corrosion ; 3 doors ; 5 seats.

	CLUB type	12 TRS type
ENGINE :	G 11/631	T 13/653
fuel :	CO/R 98	CO/R 98
cylinder capacity :	1129 cu. cm	1299 cu. cm
no. of cylinders :	4 cylinders	4 cylinders
bore x stroke :	74 x 65,6 mm	79,4 x 65,6 mm
maximum torque :	79,4 Nm/3500 rpm	9,8 mkg/3250 rpm
maximum power :	41,4 kW/6250 rpm	61,5 HP/5500 rpm
compression ratio :	9 : 1	8,7 : 1
MAX. SPEED :	146,9 km/h (5 persons) :	157 km/h (1 person)
CONSUMPTION :		
at 90 km/h	6,6 l	5,7 l
at 120 km/h	9,2 l	7,7 l
city traffic	8,8 l	8,6 l

COOLING : air cooling by continuous duty fan.

CLUTCH : dry single-disk, mechanically controlled type.

GEAR BOX : - CLUB : 4 synchronized forward speeds + a reverse one ;
- 12 TRS : 5 synchronized forward speeds + a reverse one.

SUSPENSION : front : independent type with torsion bars and transverse flexion blades, telescopic hydraulic shock-absorbers ; rear : independent type with torsion bars, hydraulic telescopic shock-absorbers.

BRAKES : service brake : hydraulic, dual circuit, front and rear disks, limiter on the rear wheels ; safety brake : mechanical on the front wheels.

STEERING : rack, central pinion.

ELECTRIC EQUIPMENT : 12 V ; 45 Ah battery ; 40 A alternator ; lighting and signalling equipment in compliance with the UNO-EEC standards.

TYRES : 145 SR 13.

FUEL TANK : 42 l .

SIZES : total length : 3732 mm ; total width : 1538 mm ; total height : 1430 mm (unladen).

WEIGHT : empty, travelling condition : 875 kg .

total, authorized weight : 1295 kg .

- on the front axle : 670 kg ;

- on the rear axle : 625 kg .

trailer :

- with braking system : 800 kg ;

- without braking system : 430 kg .

The manufacturer reserves itself the right to alter the design and auxiliary equipment of the motor car without prior notice. The mass-produced items may differ from that shown in the picture of the present leaflet.

Manufacturer :
OLTCIT Ltd.
Joint Company
Craiova — Romania

Exporter :
AUTO DACIA
Pitești — Colibași
Romania
Telephone : 976/34978
Telex : 18296 ; 18297



Exportateur :
AUTO DACIA
Pitești — Colibași
Roumanie
Téléphone : 976/34978
Télex : 18296 ; 18297

Producteur :
Société mixte OLTCIT S.A.
Craiova — Roumanie

CONSTRUCTION : moteur avant ; traction avant ; caisse en monobloc, à châssis intégré, en tôles d'acier traité par l'électrophorèse, anticorrosion ; 3 portes, 5 places

	version CLUB	version 12 TRS
MOTEUR :	G 11/631	T 13/653
carburant	CO/R 98	CO/R 98
cylindrée	1129 cm ³	1299 cm ³
nombre de cylindres :	4	4
alésage x course	74 x 65,6 mm	79,4 x 65,6 mm
couple maximal	79,4 Nm/3500 tr/mn	9,8 mkg/3250 tr/mn
puissance maximale	41,4 kW/6250 tr/mn	61,5 ch/5500 tr/mn
rapport de compression	9 : 1	8,7 : 1
CONSOMMATION :		
à 90 km /h	6,6 l	5,7 l
à 120 km/h	9,2 l	7,7 l
dans la ville	8,8 l	8,6 l
VITESSE, max. :	146,9 km/h (loge 5 personnes) :	157 km/h (loge 1 personne)

REFROIDISSEMENT : par circulation d'air, ventilateur à fonctionnement continu

EMBRAYAGE : à disque unique, sec, commande mécanique

BOÎTE DE VITESSES : 4 vitesses (CLUB) et 5 vitesses (12 TRS) ; synchronisées marche avant + marche arrière

SUSPENSION : avant : indépendante, barres de torsion et flexion à lames transversales ; arrière : indépendante, barres de torsion, amortisseurs hydrauliques télescopiques

FREINS : à main : hydraulique, double circuit, disques avant et arrière, limiteur aux roues arrière ; de secours : mécanique, de roues avant

MÉCANISME DE DIRECTION : à crémaillère, pignon central

DOTATION ÉLECTRIQUE : 12 V ; batterie 45 Ah ; alternateur 40 A ; équipement d'éclairage et de signalisation selon les normes C.E.E.

PNEUS : 145 SR 13

RESERVOIR DE CARBURANT : 42 l

DIMENSIONS : longueur totale : 3732 mm ; largeur totale : 1538 mm ; hauteur totale : 1430 mm (sans charge)

POIDS : à vide, en ordre de marche : 875 kg

total, autorisé : 1295 kg

- sur l'essieu avant : 670 kg

- sur l'essieu arrière : 625 kg

remorque :

- à système de freinage : 800 kg

- sans système de freinage : 430 kg.

Le producteur se réserve le droit de modifier la construction et les dotations de la voiture de tourisme sans aucune obligation d'avis préalable. Les produits de série peuvent être différents de celui présenté dans la photo de ce prospectus.