



Convertible
3000S

TVR

Convertible

3000S

The return of the true sports car.

The TVR Convertible 3000S. Unique. Traditional sports car performance and handling. Pedigree styling and handbuilt luxury. Tubular backbone chassis and non-rust glass-fibre body, plus foldaway hood and removable sidescreens.

For your life on the Open road.

The TVR Convertible Turbo. Penetrates established barriers of sports car performance; 140+mph, 60mph in under six seconds.

The ultimate moving experience.

The only turbo-charged open sports car in the world.



The Open Secret



The TVR Convertible 3000S is the complete open sports car:

The power unit is the familiar lusty 3-litre V6, renowned for its performance and flexibility.

Deep pile carpets, craftsman tailored trim, full traditional instrumentation, reclining seats, removable side-screens and fully detachable hood are all standard features.

The boot has an electrically operated lock neatly located in the door shut, and for added convenience map pockets are featured in the doors, and storage facilities in the dash and centre console. Luggage accommodation is further increased as the boot area is also accessible from within the car, through a lockable panel behind the seats.



TVR



*The Best of both worlds
in the true British tradition*



Convertible 3000S Specification

ENGINE:
Cylinders Vee 6
Bore 93.97 mm
Stroke 72.41 mm
Cubic Capacity 2994 cc.
Compression Ratio 8.9:1
Fuel Pump AC Mechanical
Oil Filter AC Full Flow
Carburettor Dual Choke Weber
Max. Power 142 bhp Nett at 5000 rpm
Max. Torque 172 lb.ft. at 3000 rpm

SPEED IN GEARS AT 6000 rpm.
4th* 212.8 kph (133 mph)
3rd 150.4 kph (94 mph)
2nd 108.8 kph (68 mph)
1st 67.2 kph (42 mph)
*Depending on conditions

PERFORMANCE Approx.
0-96 kph (0-60 mph) 7.5 sec
Maximum Speed 201+ kph (125+ mph)
Fuel Consumption 11.36-9.47 l. x 100 km
(25-30 mpg)

BRAKES:
Disc Front 276.225 mm (10.875") dia.
Drum Rear 228.6 mm (9") x 44.45 mm (1 3/4")
Dual Circuit Servo-Assisted

SUSPENSION:
Front Independent & Double WISHBONES Coil Springs
Rear Independent & Double WISHBONES Coil Springs

STEERING:
Rack and Pinion

WHEELS AND TYRES:
6JK x 14" dia, TVR Aluminium Alloy
185 x 14HR Radial Ply Tyres

BATTERY:
12 Volt Negative Earth, 58 Ah.

DIMENSIONS:
Wheelbase 2286 mm (7'6")
Track: Front 1365 mm (4'5 1/2")
Rear 1365 mm (4'5 1/2")
Overall Length 3937 mm (12'11")
Width 1625 mm (5'4")
Height 1117 mm (3'8")
Ground Clearance 140 mm (5 1/2")
Turning Circle Right 10897 mm (35'9")
Turning Circle Left 10897 mm (35'9")
Fuel Tank Capacity 54.8 litres (12 gallons)

The TVR Taimar hatchback — top of the range

Convertible Turbo Specification

As for Convertible 3000S except:

Max. Power 230 bhp @ 5500 rpm
Max. Torque 273 lb.ft. @ 3500 rpm
Max. B.M.E.P. 225 p.s.i. (Din)
Max. Safe continuous engine speed 6250 rpm,
intermittent 6500 rpm

Fuel Requirements 4/5 Star
Boost pressure automatically regulated to
8.5 p.s.i. maximum
Exhaust back pressure 7 p.s.i. maximum to
achieve boost
Fuel pressure automatically regulated to 3-4 p.s.i.
above boost pressure
Ignition Electronic
Engine oil pump uprated above 2500 rpm, with
oil cooler in circuit

SPEED IN GEARS AT 6500 rpm
4th* 224 kph (140 mph)
3rd 160 kph (105 mph)
2nd 116 kph (72 mph)
1st 72 kph (45 mph)
*Depending on conditions

PERFORMANCE Approx.
0-96 kph (0-60 mph) 6.0 secs.
Maximum Speed 233+ kph (145+ mph)
Fuel Consumption 12.9 l. x 100 km
(22 mpg) nominal

WHEELS AND TYRES:
6JK x 14" dia, TVR Aluminium Alloy
195 x 14 VR Radial

Specifications vary for different markets
worldwide


Turbo versions of the Convertible 3000S and
Taimar hatchback are not available in the
USA

TVR Engineering Limited reserve the right to
alter, without prior notice, specifications and
prices of any product manufactured by
them.



Convertible

3000S



TVR Engineering Limited
Bristol Avenue
Blackpool England FY2 0JF
Telephone 0253-56151
Telex 67519

Sole importer to the USA:
TVR Cars of America Limited
29 New York Avenue
Huntington
New York 11743 USA
Telephone 516 423 6333
Telex 203 144568

TVR